



**Nanjing Hunsone CNC Machine Manufactory Co., Ltd.**  
 Address: Mingjue Industrial Park, Nanjing City, Jiangsu Province, China  
 Web: [www.hunsone.com](http://www.hunsone.com) | E-mail: [sales06@hunsone.com](mailto:sales06@hunsone.com)

## QUOTATION

No:Hunsone20251023  
 Date: 2025/10/23

No.	Picture	Model	QTY (set)
1		Hydraulic press brake WE67K 200T3200mm with Delem DA58TX 4+1 axes with DSP laser safety	1
2		Hydraulic press brake WE67K 200T3200mm with Delem DA66s 6+1 axes with DSP laser safety	1
3		Hydraulic press brake WE67K 250T3200mm with Delem DA58TX 4+1 axes with DSP laser safety	1
4		Hydraulic press brake WE67K 250T3200mm with Delem DA66s 6+1 axes with DSP laser safety	1
<b>TOTAL PRICE</b>			
Press brake standard configuration: Delem DA58TX 4+1 axes (Y1,Y2,X,R+V)			
Back gauge moving X axis (front and back) R axis (up and down)		One-key release fast clamp	Germany SIEMENS main motor
		Taiwan HIWIN Ball screw and linear guide	
		Foot switch	
	<p>Delem DA58TX            2D graphical touch screen programming            18,5" high resolution color TFT            Bend sequence calculation            Crown control            Servo and frequency inverter control            Advanced Y-axis control algorithms for closed-loop as well as open-loop valves.            USB, peripheral interfacing            Profile-T offline software</p>		

Press brake options:

		<p>Delem DA66S</p> <p>2D graphical touch screen programming mode</p> <p>3D machine representation, in simulation and production</p> <p>24" high resolution color TFT</p> <p>Delem Modusys compatibility (module scalability and adaptivity)</p> <p>USB, peripheral interfacing</p> <p>User specific application support within the control's multitasking environment</p> <p>Sensor bending &amp; correction interface</p> <p>Profile-S2D offline software</p>		
		<p>Delem DA69S</p> <p>3D and 2D graphical touch screen programming mode</p> <p>3D visualization, including 3D machine representation, in simulation and production</p> <p>24" high resolution color TFT</p> <p>Delem Modusys compatibility (module scalability and adaptivity)</p> <p>USB, peripheral interfacing</p> <p>User specific application support within the control's multitasking environment</p> <p>Sensor bending &amp; correction interface</p> <p>Profile-S3D offline software</p>		
 <p>BACKGAUGE 2 AXES* Backgauge with X and R axes X1,X2 axes (front and back)</p>	 <p>BACKGAUGE 4 AXES* BackGauge with X, R,Z1,Z2 axes</p>	 <p>BACKGAUGE 6 AXES* BackGauge with X1 X2 R1 R2 Z1 Z2 axes</p>		
Back gauge moving X axis (front and back) R axis (up and down)	Back gauge moving X axis (front and back) R axis (up and down) Z1,Z2 axes (stop finger moving left and right)	Back gauge moving X1,X2 axes (front and back) R1,R2 axes (up and down) Z1,Z2 axes (stop finger moving left and right)		
1		backgauge YASKAWA servo motor		
2		Main Inovance servo motor	1	
3		Hybrid Inovance servo motor	1	
4		MSD laser safety	1	
5		DSP laser safety	1	
6		DSP-AP laser safety	1	
7		Valve monitoring (Rexroth three-point type)The three points are: overall fast down, overall slow down, overall return.	1	
8		DZDY upper hydraulic clamping 2500mm	1	
9		DZDY upper hydraulic clamping 3200mm	1	
10		DZDY upper hydraulic clamping 4000mm	1	
11		DZDY low hydraulic clamping 2500mm	1	
12		DZDY low hydraulic clamping 3200mm	1	
13		DZDY low hydraulic clamping 4000mm	1	
14		DZDY Hydraulic pump station	1	
15		Nuoguard 180KG bending follower	1	
16		Nuoguard 380KG bending follower	1	

REMARK:

1.Payment Terms: T/T 30% deposit and the balance before delivery.

2.Price Terms: FOB Shanghai

3.Lead Time: 30 working days.

4.Packing:Plastic bag cover

5.Validity Time: 30 days.